

RP076.2 ZipSpeed Trolley, 75mm (3") Wheel Diameter

Data Sheet



Colour Key

- > 13mm (1/2") Wire
- > 16mm (5/8") Wire
- > 20mm (3/4") Wire

We offer versions for 13mm (1/2"), 16mm (5/8") or 20mm (3/4") Wire and the centre redundancy axle is fitted with a colour coded collar, for easy identification.



Options/Accessories:

Stabiliser Bars

Optional Stabiliser Bars are available for the RP076 ZipSpeed-L Trolley (either as a factory-fit or retro-fit option).

The stabilizer bar accessory can be used with parallel harness webbing attachments, in order to help to prevent twist/rotation, in order to help to keep the rider facing forward. **NOTE:** the attachment points on the stabilizer bar are **NOT rated**, and should **NOT** be used as a main point of attachment.



Anti-rollback Cam [ARC]



Cam in neutral position

Cam engaged

The Anti-rollback Cam is a simple device which can be retro-fitted to the ZipSpeed Trolley. During normal use, the cam remains disengaged, allowing the trolley to roll forwards, unhindered. However, as soon as the trolley begins to roll backwards, the cam is activated, bringing the trolley to an immediate halt.

This anti-rollback function captures the progress of the trolley, which means that even when the trolley doesn't reach the end of the zipline, it cannot roll backward and hence rescue distance (and therefore, rescue time) is significantly reduced.

climb. work. rescue.

I|S|C
SOLUTIONS IN METAL

The Zipspeed Tandem Trolleys are fitted with rubber sealed bearings for optimal performance and lifespan. ZipSpeed Trolleys are fitted with Superior Grade Stainless Steel Wheels, which are heat treated, to increase their hardness. The hard wheels are designed to offer optimal support to the bearings, helping them to resist deformation.

The main attachment point is large enough to accommodate a wide variety of Karabiners & Snaphooks. There are extra attachment holes for a secondary lanyard and a small central hole which can be used to fit an accessory (stabiliser bar etc).

Weight	1793g (63oz)
Height	140mm (5 ¹ / ₂ ')
Width	280mm (11")
Depth	31mm (1 ¹ / ₄ ')
Body Material	Aluminium
Finish	Anodised
Wheel Diameter	75mm (3")
Wheel Material	Stainless Steel
MBS	40kN (8992lbf)